



AYAA TECHNOLOGY CO.,LTD

PCM Specifications

Model: PCM-LX5S7A-AY041 (LI-5S7A)

Test item		Criterion	
		Lifepo4	Li-ion/Li-polymer
Voltage	Charging voltage	DC 18V CC/CV(3.6V/cell)	DC:21V CC/CV(4.2V/cell)
	Balance voltage for single cell	/	/
Current	Current consumption for single cell	≤50μA	≤50μA
	Maximal continuous charging current	7A	7A
	Maximal continuous discharging current	7A	7A
	Balance current for single cell	/	/
Over charge Protection (single cell)	Over charge detection voltage	3.90V±0.025V	4.25±0.025V
	Over charge detection delay time	0.5-2.0S	0.5S—2.0S
	Over charge release voltage	3.805±0.1V	4.05 ±0.1V
Over discharge protection (single cell)	Over discharge detection voltage	2.00±0.8V	2.5±0.08V
	Over discharge detection delay time	10-200mS	10-200mS
	Over discharge release voltage	2.3±0.1V	3.0±0.1V
Over current protection (Battery pack)	Over current detection current	final data fixed from actual test	final data fixed from actual test
	Over current detection voltage	depend on the above points	depend on the above points
	Detection delay time	5-50ms	5-50ms
	Release condition	Cut load,Auto release	Cut load,Auto release
Short protection	Detection condition	Exterior short circuit	
	Detection delay time	200~600us	
	Release condition	charge up	
Resistance	Protection circuitry	≤50mΩ	
Temperature	Operating Temperature Range	-40~+85℃	
	Storage Temperature Range	-40~+125℃	

SIZE: L82*W16*T3mm

Optional Parameters:	Over charge detection voltage (V)	4.28±0.025V	4.25±0.025V	3.65±0.025V
	Over charge release voltage(V)	4.10±0.05V	4.05±0.05V	3.65±0.05V
	Over discharge detection voltage	3.00±0.8V	2.80±0.8V	2.50±0.8V
	Over discharge release voltage(V)	3.20±0.1V	3.00±0.1V	3.00±0.1V

