



AYAA TECHNOLOGY CO.,LTD

PCM Specifications

Model: PCM-L03S04-730 (LI-3S4A)

Test item (Test at normal temperature 25±2℃)		Criterion
Voltage	Charging voltage	DC: 12.6V CC/CV (4.2v/Cell) 3s
Supply Current	Normal operating mode current: Fuel gauge in NORMAL mode. ILOAD > Sleep Current	≤50uA
	Maximal continuous charging current	4A
	Maximal continuous discharging current	4A
	Balance current for single cell	/
Over-charge Protection (single cell)	Balance voltage for single cell	/
	Over charge detection voltage	4.35±0.05V
	Over charge detection delay time	0.5S—2S
	Over charge release voltage	4.10±0.1V
Over discharge protection (single cell)	Over discharge detection voltage	2.40±0.05V
	Over discharge detection delay time	10—200mS
	Over discharge release voltage	3.0±0.1V
Over current protection	Discharge Over current detection current	10±3A
	Detection delay time	5ms—50ms
	Release condition	Cut load,Auto Recovery
Short protection	Detection condition	Exterior short circuit
	Detection delay time	200-500us
	Release condition	Cut load
Resistance	Protection circuitry (MOSFET)	≤20mΩ
Temperature	Operating Temperature Range	-40~+85℃
	Storage Temperature Range	-40~+125℃

SIZE: L32 *W32 *T3.5 mm

NTC: / Temperature switch: / Weak current switch: / Activation Method:/

