



AYAA TECHNOLOGY CO.,LTD



PCM Specifications

Model: PCM-LX2S2A-AY321 (LI-2S2A) Ver: A

Test item (Test at normal temperature 25±2℃)		Criterion
Voltage	Charging voltage	DC: 8.4V CC/CV (4.2V/Cell) 2s
Supply Current	Normal operating mode current: Fuel gauge in NORMAL mode. ILOAD > Sleep Current	≤10uA
	Maximal continuous charging current	2A
	Maximal continuous discharging current	2A
Over-charge Protection (single cell)	Over charge detection voltage	4.25±0.05V
	Over charge detection delay time	0.5S—2S
	Over charge release voltage	4.05±0.1V
Over discharge protection (single cell)	Over discharge detection voltage	2.4±0.05V
	Over discharge detection delay time	100—200mS
	Over discharge release voltage	3.0±0.1V
Current protection (Battery pack)	ChargeOver current detection current	/
	Detection delay time	/
	Discharge Over current detection current	5±2A
	Detection delay time	5ms—20ms
	Release condition	Cut load, Auto Recovery
Short protection	Detection condition	Exterior short circuit
	Detection delay time	200-600us
	Release condition	Cut load
Resistance	Main loop electrify resistance	≤ 65mΩ
Temperature	Operating Temperature Range	-40~+85℃
	Storage Temperature Range	-40~+125℃

SIZE: L34*W17*T3 mm **P+/P- 2 contacts on top 12mm diameter "hard gold"**

NTC: / Temperature switch: / Weak current switch: / Activation Method: /



Prepared: Cassie 2020-10-21

Checked:

Approved: